

BS2_GetSpecifiedDeviceInfo 1
..... 1
..... 1
..... 1

BS2_GetSpecifiedDeviceInfo

[+ 2.6.3] specifiedDeviceInfo

가

```
#include "BS_API.h"

int BS2_GetSpecifiedDeviceInfo(void* context, uint32_t deviceId,
BS2EnumSpecifiedDeviceInfo specifiedDeviceInfo, void* pOutDeviceInfo,
uint32_t nDeviceInfoSize, uint32_t* pOutDeviceInfoSize);
```

- BS2SimpleDeviceInfo
- BS2SimpleDeviceInfoEx
- BS2IPv6DeviceInfo


- [In] *context* : Context
- [In] *deviceId* :
- [In] *specifiedDeviceInfo* :

1	BS2SimpleDeviceInfo
2	BS2SimpleDeviceInfoEx
3	BS2IPv6DeviceInfo

- [Out] *pOutDeviceInfo* :
- [In] *nDeviceInfoSize* :
- [Out] *pOutDeviceInfoSize* :

BS_SDK_SUCCESS

, 가



From:

<https://kb.supremainc.com/bs2sdk/> - **BioStar Device SDK**

Permanent link:

https://kb.supremainc.com/bs2sdk/doku.php?id=ko:bs2_getspecifieddeviceinfo

Last update: **2019/05/13 18:12**