

BS2_SetSlaveBaudrate 1
ÇÔ¼ö 1
ÆÄ¶óìÁí 1
¹ÝÈ[°] 1

BS2_SetSlaveBaudrate

[+ 2.9.8] , ¶½°ÁÍ ÀãÄi¿i ¿¬°áµÈ ½½½·¹Àì°è ÀãÄiÀÇ RS-485 Äü¼¼Û ¼¼Óµµ,¡ °¬°æÇÕ´Í´Û.
½½½·¹Àì°è¿í ´Û½½Ä ¿¬°áÇĪ·Á,é , ¶½°ÁÍ ÀãÄiÀÇ RS-485 Äü¼¼Û ¼¼Óµµµµ ½½½·¹Àì°èÀÇ Äü¼¼Û¼¼Óµµ¿í
µ¿ÄĪÇĪ°Ô °¬°æÇØ¾¼ß ÇÕ´Í´Û.

ÇÕ¼¼ö

```
#include "BS_API.h"

int BS2_SetSlaveBaudrate(IntPtr context, UInt32 deviceId, UInt32 slaveId,
                          UInt32 baudrate);
```

ÆÄ¶ó¹ÄÍ

- [In] *context* : Context
- [In] *deviceId* : ÀãÄi ½Ä°°ÀÚ
- [In] *slaveId* : ½½½·¹Àì°è ÀãÄi ½Ä°°ÀÚ
- [In] *baudrate* : RS-485 Åë½½Å ¼¼Óµµ

¹ÝÈ¬°a

¼¼°°ØÀÛÄ,·Í ¼¼öÇàµÉ °æ¿ì BS_SDK_SUCCESS,¡ ¹ÝÈ¬ÇĪ°í, ¿i·¬°i ¹ß»ýÇÒ °æ¿ì »óÀÄÇĪ´Ä ¿i·¬ ÄÜµå,¡
¹ÝÈ¬ÇÕ´Í´Û.

From:
<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:
http://kb.supremainc.com/bs2sdk/doku.php?id=ko:bs2_setslavebaudrate&rev=1729745033

Last update: **2024/10/24 13:43**