

BS2_SetSlaveBaudrate 1
ÇÔ¼ö 1
ÆÄ¶óìÁí 1
¹ÝÈ[°]ä 1

BS2_SetSlaveBaudrate

[+ 2.9.8] , ¶½°ÁÍ ÀãÄi¿i ¿¬°áµÈ ½½½·¹Àì°è ÀãÄiÀÇ RS-485 Àü¼¼Ù ¼¼Óµµ,| °¬°æÇÕ´Í´Ù. ½½½·¹Àì°è¿í ´Ù½½Ä ¿¬°áÇĪ·Á,é , ¶½°ÁÍ ÀãÄiÀÇ RS-485 Àü¼¼Ù ¼¼Óµµµµ ½½½·¹Àì°èÀÇ Àü¼¼Ù¼¼Óµµ¿í µ¿ÄĪÇĪ°Ô °¬°æÇØ¾¼ß ÇÕ´Í´Ù.

ÇÕ¼¼ö

```
#include "BS_API.h"

int BS2_SetSlaveBaudrate(IntPtr context, UInt32 deviceId, UInt32 slaveId, UInt32 baudrate);
```

ÆÄ¶ó¹ÄÍ

- [In] *context* : Context
- [In] *deviceId* : ÀãÄi ½Ä°ÀÚ
- [In] *slaveId* : ½½½·¹Àì°è ÀãÄi ½Ä°ÀÚ
- [In] *baudrate* : RS-485 Åë½Ä ¼¼Óµµ

¹ÝÈ¬°a

¼¼°øÀÙÀ,·Ī ¼¼öÇàµÉ °æ¿ì BS_SDK_SUCCESS,| ¹ÝÈ¬ÇĪ°í, ¿i·¬°i ¹ß»ýÇÒ °æ¿ì »óÀÀÇĪ·Ä ¿i·¬ ÄÚµå,| ¹ÝÈ¬ÇÕ´Í´Ù.

From:
<http://kb.supremainc.com/bs2sdk/> - **BioStar Device SDK**

Permanent link:
http://kb.supremainc.com/bs2sdk./doku.php?id=ko:bs2_setslavebaudrate&rev=1729745033

Last update: **2024/10/24 13:43**