

**Communication API** ..... 1  
..... 1

# Communication API

API

LAN, USB, RS485

## BS2\_SetDeviceEventListener

- [BS2\\_SetDeviceEventListener](#): Event listener
- [BS2\\_SearchDevices](#): Subnet
- [BS2\\_SearchDevicesEx](#): IP
- [BS2\\_GetDevices](#): 가
- [BS2\\_ConnectDevice](#):
- [BS2\\_ConnectDeviceViaIP](#): IP Port
- [BS2\\_DisconnectDevice](#):
- [BS2\\_SetKeepAliveTimeout](#): Keep-alive timeout
- [BS2\\_SetNotificationListener](#): Notification listener
- [BS2\\_SetServerPort](#): Server Port
- [BS2\\_SetSSLServerPort](#): Server SSL Port
- [BS2\\_GetServerPort](#): [+ 2.6.3] Server Port
- [BS2\\_GetSSLServerPort](#): [+ 2.6.3] Server SSL Port
- [BS2\\_IsConnected](#):
- [BS2\\_IsAutoConnection](#):
- [BS2\\_SetAutoConnection](#):
- [BS2\\_GetEnableIPv4](#): [+ 2.6.3] IP V4
- [BS2\\_SetEnableIPv4](#): [+ 2.6.3] IP V4
- [BS2\\_GetEnableIPv6](#): [+ 2.6.3] IP V6
- [BS2\\_SetEnableIPv6](#): [+ 2.6.3] IP V6
- [BS2\\_SetServerPortIPv6](#): [+ 2.6.3] IP V6 port
- [BS2\\_GetServerPortIPv6](#): [+ 2.6.3] IP V6 port
- [BS2\\_SetSSLServerPortIPv6](#): [+ 2.6.3] IP V6 ssl port
- [BS2\\_GetSSLServerPortIPv6](#): [+ 2.6.3] IP V6 ssl port
- [BS2\\_SetDefaultResponseTimeout](#): [+ 2.6.3]
- [BS2\\_GetDefaultResponseTimeout](#): [+ 2.6.3]

```
typedef void (*OnDeviceFound)(uint32_t deviceId);
typedef void (*OnDeviceAccepted)(BS2_DEVICE_ID deviceId);
typedef void (*OnDeviceConnected)(uint32_t deviceId);
typedef void (*OnDeviceDisconnected)(uint32_t deviceId);
typedef void (*OnAlarmFired)(BS2_DEVICE_ID deviceId, const BS2Event* event);
typedef void (*OnInputDetected)(BS2_DEVICE_ID deviceId, const BS2Event* event);
typedef void (*OnConfigChanged)(BS2_DEVICE_ID deviceId, uint32_t configMask);
```

## 1. OnDeviceFound

Subnet            BioStar

2. *OnDeviceAccepted*

BioStar    가 BioStar

3. *OnDeviceConnected*

BioStar

4. *OnDeviceDisconnected*

BioStar

5. *OnAlarmFired*

Zone

6. *OnInputDetected*

가

7. *OnConfigChanged*

Configuration

From:

<https://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

[https://kb.supremainc.com/bs2sdk./doku.php?id=ko:communication\\_api&rev=1558933121](https://kb.supremainc.com/bs2sdk./doku.php?id=ko:communication_api&rev=1558933121)

Last update: **2019/05/27 13:58**