

2.4.0		1
-------	-------	---

2.4.0

2017-3-24

BioStar 2 Device SDK v2.4가 2.4 .

v2.4

- [BS2_EnrollUserEx](#)가 가 .
- [BS2_GetUserInfosEx](#)가 가 .
- [BS2UserBlobEx](#)가 가 .
- [SSL API](#)가 가 .

v2.4

BioStation 2	1.4.0
BioStation A2	1.3.0
BioStation L2	1.2.0
BioEntry W2	1.1.0

1. OM-120 SDK API가 가 .
 - [Lift Control API](#)가 가 .OM-120 Lift 12 Relay door Access group floor level . floor level OM-120 Access level .
2. FaceStation 2 2017 2 . v2.4 FaceStation 2 7 .

- Face API 가 가 .

FaceStation 2 1:N Matching 5,000

3. v1 Template . v1 v2 가
 , v1 ./

- BS1CardConfig 가 가 .

v1 ToC(Template on Card)가 v2 . v2
 block index가 v1 CIS index block . v1 ToC v2
 Access on Card/Secure Credential Card , block index CIS index
 block .

4. T&A SW Job Code가 가 . Job Code
 Job Code . v2.4 FW .

- BS2UserBlobEx 가 가 .

BS2UserBlob

BS2UserBlobEx Job Code v2.4 FW .
 Job Code .

5. 가 .

- API BS2_GetLogBlob 가 가 .
- BS2EventBlob 가 가 .

API BS2_GetLog Job Code 가 . blob 가
 API가 . blob
 가 .

6. FW .

- BS2UserBlobEx 가 가 .

FaceStation 2 .

BS2UserBlobEx

BS2UserBlobEx v2.4 FW .

7. SSL 가 . SSL , 가 가

- SSL API 가 가 .

1. **outQuality** 가 [BS2_ScanFingerprint](#) API 가 .
[BS2_ScanFingerprint](#) API 가 가 .
 가

BEFORE

```
#include "BS_API.h"

int BS2_ScanFingerprint(void* context, uint32_t deviceId, BS2Fingerprint*
finger, uint32_t templateIndex, uint32_t quality, uint8_t templateFormat,
OnReadyToScan ptrReadyToScan);
```

AFTER

```
#include "BS_API.h"

int BS2_ScanFingerprint(void* context, uint32_t deviceId, BS2Fingerprint*
finger, uint32_t templateIndex, uint32_t quality, uint8_t templateFormat,
uint32_t* outQuality, OnReadyToScan ptrReadyToScan);
```

2. **useJobCode, useAlphanumericID, cameraFrequency** 가 [BS2SystemConfig](#)
 가 .
useJobCode Job Code Enable/Disable 가 .
 ID BioStation 2, BioStation A2, BioStation L2 BioEntry W2 가
 ID + Credential 가
 . v2.4 FW **useAlphanumericID** </ text>
 가 ID .
 <text type = "success"> **cameraFrequency** </ text> BioStation
 A2 .

<text size="x-large">3. **rs485mode, sslSupported, rootCertExist, dualIDSupported,**
useAlphanumericID, connectedIP, phraseCodeSupported, card1xSupported,
systemExtSupported, voipSupported 가 [BS2SimpleDeviceInfo](#) 가 .
[BS2SimpleDeviceInfo](#) 가 가 .

rs485mode RS-485 .
sslSupported 가 SSL .
rootCertExist 가 .
dualIDSupported 가 Dual ID .
useAlphanumericID 가 ID .
connectedIP 가 IP .
phraseCodeSupported 가 .

card1xSupported 가 v1 ToC
 systemExtSupported 가 RS-485
 voipSupported 가 VoIP

1. UDP 가 v2.4 FW . SDK

2. [BS2_GetConfig](#) 가 가
[BS2MultiWiegandConfig](#) 가 가
 가

3. BioEntry Plus BioEntry W wiegand SDK
 wiegand

From:

<https://kb.supremainc.com/bs2sdk/> - **BioStar Device SDK**

Permanent link:

https://kb.supremainc.com/bs2sdk/doku.php?id=ko:release_note_240&rev=1519176760

Last update: **2018/02/21 10:32**