

2.4.0 ..... 1

# 2.4.0

2017-3-24

BioStar 2 Device SDK v2.4 가 2.4 .

v2.4

- [BS2\\_EnrolUserEx](#) 가 가 .
- [BS2\\_GetUserInfosEx](#) 가 가 .
- [BS2UserBlobEx](#) 가 가 .
- [SSL API](#)가 가 .

v2.4

BioStation 2	1.4.0
BioStation A2	1.3.0
BioStation L2	1.2.0
BioEntry W2	1.1.0

1. OM-120 SDK  
 API 가 가 .

- [Lift Control API](#) 가 가 .

OM-120 Lift 12 Relay door  
 Access group floor level floor level Access level

2. FaceStation 2 2017 2 . v2.4 FaceStation 2  
 7 .

- Face API 가 가

FaceStation 2 1:N Matching 5,000

3. v1 Template . v1 v2 가  
v1

- BS1CardConfig 가 가

v1 ToC(Template on Card)가 v2 . v2  
block index가 v1 CIS index block . v1 ToC v2  
Access on Card/Secure Credential Card , block index CIS index  
block

4. T&A SW Job Code가 가 . Job Code  
Job Code v2.4 FW

- BS2UserBlobEx 가 가

BS2UserBlob  
BS2UserBlobEx Job Code v2.4 FW  
Job Code

5. 가

- BS2\_GetLogBlob 가 가
- BS2EventBlob 가 가

API BS2\_GetLog Job Code 가 blob 가  
API가 blob  
가

6. FW

- BS2UserBlobEx 가 가

FaceStation 2

BS2UserBlobEx  
BS2UserBlobEx v2.4 FW

7. SSL 가 . SSL , 가 가

- SSL API 가 가

1. **outQuality** 가 [BS2\\_ScanFingerprint API](#) 가 . 가 가 .  
[BS2\\_ScanFingerprint API](#) 가 가 .  
 가

```
#include "BS_API.h"

int BS2_ScanFingerprint(void* context, uint32_t deviceId, BS2Fingerprint*
finger, uint32_t templateIndex, uint32_t quality, uint8_t templateFormat,
OnReadyToScan ptrReadyToScan);
```

```
#include "BS_API.h"

int BS2_ScanFingerprint(void* context, uint32_t deviceId, BS2Fingerprint*
finger, uint32_t templateIndex, uint32_t quality, uint8_t templateFormat,
uint32_t* outQuality, OnReadyToScan ptrReadyToScan);
```

2. **useJobCode, useAlphanumericID, cameraFrequency** 가 [BS2SystemConfig](#)

가 .  
**useJobCode** Job Code Enable/Disable 가 .  
 ID BioStation 2, BioStation A2, BioStation L2 BioEntry W2 가  
 ID + Credential 가  
 . v2.4 FW **useAlphanumericID**  
 가 ID  
**cameraFrequency** BioStation A2 .

3. **rs485mode, sslSupported, rootCertExist, dualIDSupported,**  
**useAlphanumericID, connectedIP, phraseCodeSupported, card1xSupported,**  
**systemExtSupported, voipSupported** 가 [BS2SimpleDeviceInfo](#) 가 .  
[BS2SimpleDeviceInfo](#) 가 가 .

- **rs485mode** RS-485
- **sslSupported** 가 SSL
- **rootCertExist** 가
- **dualIDSupported** 가 Dual ID
- **useAlphanumericID** 가 ID
- **connectedIP** 가 IP
- **phraseCodeSupported** 가

