

**SDK API** ..... 1  
..... 1  
BS2EncryptKey ..... 1  
BS2LicenseBlob ..... 2  
BS2LicenseResult ..... 2

# SDK API

- [BS2\\_Version](#): SDK
- [BS2\\_AllocateContext](#): Context
- [BS2\\_ReleaseContext](#): Context
- [BS2\\_Initialize](#): Context
- [BS2\\_ReleaseObject](#):
- [BS2\\_MakePinCode](#): PIN
- [BS2\\_MakePinCodeWithKey](#): PIN . [+ 2.7.1]
- [BS2\\_SetMaxThreadCount](#):
- [BS2\\_ComputeCRC16CCITT](#): CRC-16 CCITT
- [BS2\\_GetCardModel](#): 가
- [BS2\\_SetDataEncryptKey](#): PIN . [+ 2.7.1]
- [BS2\\_RemoveDataEncryptKey](#):
- [BS2\\_SetDeviceSearchingTimeout](#):
- [BS2\\_SetDebugFileLog](#):
- [BS2\\_SetDebugFileLogEx](#): ( 가 ) [+ 2.8.3]
- [BS2\\_EnableDeviceLicense](#): [+ 2.9.1]
- [BS2\\_DisableDeviceLicense](#): [+ 2.9.1]
- [BS2\\_QueryDeviceLicense](#): [+ 2.9.1]
- [BS2\\_InitializeEx](#): [+ 2.9.6] Context

## BS2EncryptKey

```
enum
{
    BS2_ENC_KEY_SIZE = 32,
};

typedef struct
{
    uint8_t key[BS2_ENC_KEY_SIZE];
    uint8_t reserved[32];
} BS2EncryptKey;
```

1. *key*

2. *reserved*

## BS2LicenseBlob

```
typedef struct {
    BS2_LICENSE_TYPE    licenseType;
    uint16_t            numOfDevices;
    BS2_DEVICE_ID*     deviceIDObjs;
    uint32_t            licenseLen;
    uint8_t*           licenseObj;
} BS2LicenseBlob;
```

### 1. licenseType

0x0000	None
0x0001	Visual QR

### 2. numOfDevices

### 3. deviceIDObjs

가 slave

### 4. licenseLen

### 5. licenseObj

## BS2LicenseResult

```
typedef struct {
    BS2_DEVICE_ID    deviceID;
    BS2_LICENSE_STATUS status;
} BS2LicenseResult;
```

### 1. deviceID

### 2. status

0	Not supported ( )
1	Disable ( )
2	Enable ( )
3	Expired ( )

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

[http://kb.supremainc.com/bs2sdk/doku.php?id=ko:sdk\\_api](http://kb.supremainc.com/bs2sdk/doku.php?id=ko:sdk_api)

Last update: **2024/02/27 14:59**