

SDK API 1
..... 1
 BS2CredentialKeyInfo 1

SDK API

PIN

API

- [BS2_Version](#): SDK
- [BS2_AllocateContext](#): Context
- [BS2_ReleaseContext](#): Context
- [BS2_Initialize](#): Context
- [BS2_ReleaseObject](#):
- [BS2_MakePinCode](#): PIN
- [BS2_SetMaxThreadCount](#):
- [BS2_ComputeCRC16CCITT](#): CRC-16 CCITT
- [BS2_GetCardModel](#): 가
- [BS2_GetCredentialKeyInfo](#): 가
- [BS2_SetCredentialKeyInfo](#):
- [BS2_RemoveCredentialKeyInfo](#):

BS2CredentialKeyInfo

```

/**
 * BS2_CRED_KEY_REQ
 */
enum
{
    BS2_CRED_KEY_REQ_COMM = ,
    BS2_CRED_KEY_REQ_DATA = 1,
};

enum
{
    BS2_CRED_KEY_SIZE = 32,
};

/**
 * BS2CredentialKeyInfo
 */
typedef struct
{
    uint32_t maxPacketSize;           ///< 4 bytes
    uint8_t  key[BS2_CRED_KEY_SIZE];  ///< 32 bytes
    uint8_t  dualIDSupported;         ///< 1 byte
    uint8_t  useAlphanumericID;       ///< 1 byte
    uint8_t  credentialKeySupported;  ///< 1 byte
}

```

```

uint8_t credentialKeyRequest;    ///< 1 byte
uint8_t reserved[28];          ///< 28 bytes (reserved)
} BS2CredentialKeyInfo;

```

1. *maxPacketSize*

가 TCP

2. *key*

credentialKeyRequest

3. *dualIDSupported*

userID (,)

4. *useAlphanumericID*

alphanumeric userID flag

5. *credentialKeySupported*

FW release 가 2018.03.30

가

6. *credentialKeyRequest*

FW release 가 2018.03.30

FW

BS2_CRED_KEY_REQ_COMM	
BS2_CRED_KEY_REQ_DATA	

7. *reserved*

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk./doku.php?id=ko:sdk_api&rev=1521779237

Last update: **2018/03/23 13:27**