2024/05/17 10:52 1/1 Server API

Table of Contents

Server API	1
Callback Function	 1
OnlicarPhrace	7

2024/05/17 10:52 1/2 Server API

Server API

API that can enable server matching or controls the device from the BioStar application.

Warning

Due to the issues with the management of UFMatcher.dll which was provided by a separate independent Corporation, Runnable examples will not be available anymore. Please reference the prior examples at the code level only.

Other technical supports including libraries for server matching can be provided by SupremaID sales team.

<wrap hi>SupremalD : sales_id@supremainc.com</wrap>

- BS2_SetServerMatchingHandler: Registers the server matching handler.
- BS2_VerifyUser: Transfers user information mapped to the card or user ID authentication results to the device.
- BS2_IdentifyUser: Transfers user information mapped to the fingerprint authentication results to the device.
- BS2_VerifyUserEx: [+ 2.4.0] Transfers user information mapped to the card or user ID authentication results to the device.
- BS2_IdentifyUserEx: [+ 2.4.0] Transfers user information mapped to the fingerprint authentication results to the device.
- BS2_VerifyUserSmall: [+ 2.6.3] Transfers user information mapped to the card or user ID authentication results to the device.
- BS2_IdentifyUserSmall: [+ 2.6.3] Transfers user information mapped to the fingerprint authentication results to the device.
- BS2_VerifyUserSmallEx: [+ 2.6.3] Transfers user information mapped to the card or user ID authentication results to the device.
- BS2_IdentifyUserSmallEx: [+ 2.6.3] Transfers user information mapped to the fingerprint authentication results to the device.
- BS2_VerifyUserFaceEx: [+ 2.7.2] Transfers user information mapped to the card or user ID authentication results to the device.
- BS2 SetUserPhraseHandler: [+ 2.7.0] Registers the server user phrase handler.
- BS2 ResponseUserPhrase: [+ 2.7.0] Transfers the user phrase to the device.

Callback Function

```
typedef void (*OnVerifyUser)(uint32_t deviceId, uint16_t seq, uint8_t
isCard, uint8_t cardType, const uint8_t* data, uint32_t dataLen);
typedef void (*OnIdentifyUser)(uint32_t deviceId, uint16_t seq, uint8_t
format, const uint8_t* templateData, uint32_t templateSize);
```

2024/05/17 10:52 2/2 Server API

1. OnVerifyUser

Callback function that is called when the BioStar application needs to distinguish whether the card or user ID matches.

2. OnldentifyUser

Callback function that is called when the BioStar application needs to distinguish whether the fingerprint matches.

OnUserPhrase

Callback function asking for user phrase to the server.

```
typedef void (*OnUserPhrase)(uint32_t deviceId, uint16_t seq, const char*
userID);
```

1. deviceId

Device ID

2. seq

Packet sequence

3. userID

User ID

From:

https://kb.supremainc.com/bs2sdk/ - BioStar 2 Device SDK

Permanent link:

https://kb.supremainc.com/bs2sdk/doku.php?id=en:server_api&rev=1628205725

Last update: 2021/08/06 08:22