

Door Control API	1
.....	1
BS2DoorRelay	1
BS2DoorSensor	1
BS2ExitButton	2
BS2DoorStatus	2
BS2Door	4

Door Control API

가 , 가 , ..

- [BS2_GetDoor:](#) 가 .
- [BS2_GetAllDoor:](#) 가 .
- [BS2_GetDoorStatus:](#) 가 .
- [BS2_GetAllDoorStatus:](#) 가 .
- [BS2_SetDoor:](#) .
- [BS2_SetDoorAlarm:](#) .
- [BS2_RemoveDoor:](#) .
- [BS2_RemoveAllDoor:](#) .
- [BS2_ReleaseDoor:](#) .
- [BS2_LockDoor:](#) ,
- [BS2_UnlockDoor:](#) ,

BS2DoorRelay

```
typedef struct {
    uint32_t deviceID;
    uint8_t port;
    uint8_t reserved[3];
} BS2DoorRelay;
```

1. *deviceID*

2. *port*

port number

3. *reserved*

BS2DoorSensor

```
typedef struct {
    uint32_t deviceID;
    uint8_t port;
    uint8_t switchType;
    uint8_t reserved[2];
} BS2DoorSensor ;
```

1. *deviceId*
2. *port*
port number
3. *switchType*

0	
1	

4. *reserved*

BS2ExitButton

```
typedef struct {  
    uint32_t deviceId;  
    uint8_t port;  
    uint8_t switchType;  
    uint8_t reserved[2];  
} BS2ExitButton ;
```

1. *deviceId*
2. *port*
port number
3. *switchType*

0	
1	

4. *reserved*

BS2DoorStatus

```
typedef struct {  
    uint32_t id;  
    uint8_t opened;  
    uint8_t unlocked;  
    uint8_t heldOpened;
```

```
uint8_t unlockFlags;  
uint8_t lockFlags;  
uint8_t alarmFlags;  
uint8_t reserved[2];  
uint32_t lastOpenTime;  
} BS2DoorStatus;
```

1. *id*

2. *opened*

flag .

3. *unlocked*

flag .

4. *heldOpened*

flag .

5. *unlockFlags*

(OPERATOR),
unlockFlags lockFlags (NONE) 가

0		
1		
4		
2		

6. *lockFlags*

0		
1		
4		
2		

7. *alarmFlags*

0	
1	
4	
2	APB

8. *reserved*

9. *lastOpenTime*

BS2Door

```
typedef struct {
    uint32_t doorID;
    char name[BS2_MAX_DOOR_NAME_LEN];
    uint32_t entryDeviceID;
    uint32_t exitDeviceID;
    BS2DoorRelay relay;
    BS2DoorSensor sensor;
    BS2ExitButton button;
    uint32_t autoLockTimeout;
    uint32_t heldOpenTimeout;
    uint8_t instantLock;
    uint8_t unlockFlags;
    uint8_t lockFlags;
    uint8_t unconditionalLock;
    BS2Action forcedOpenAlarm[BS2_MAX_FORCED_OPEN_ALARM_ACTION];
    BS2Action heldOpenAlarm[BS2_MAX_HELD_OPEN_ALARM_ACTION];
    uint32_t dualAuthScheduleID;
    uint8_t dualAuthDevice;
    uint8_t dualAuthApprovalType;
    uint32_t dualAuthTimeout;
    uint8_t numDualAuthApprovalGroups;
    uint8_t reserved2[1];
    uint32_t dualAuthApprovalGroupID[BS2_MAX_DUAL_AUTH_APPROVAL_GROUP];
    BS2AntiPassbackZone apbZone;
} BS2Door;
```

1. *doorID*

2. *name*

BioStar

3. *entryDeviceID*

4. *exitDeviceID*

5. *relay*

6. *sensor*

/

7. *button*
Exit

8. *autoLockTimeout*

9. *heldOpenTimeout*

10. *instantLock*
가 flag

11. *unlockFlags*
(OPERATOR),
unlockFlags lockFlags (NONE) 가

0		
1		
4		
2		

12. *lockFlags*

0		
1		
4		
2		

13. *unconditionalLock*
autoLock timeout door lock flag

0	autoLock timeout door close door lock . (door open door가 close)
1	autoLock timeout door open/close door lock

14. *forcedOpenAlarm*
5

15. *heldOpenAlarm*
5

16. *dualAuthScheduleID*
0 , 1 ,

17. *dualAuthDevice*
가 flag .

0	
1	
2	
3	

18. *dualAuthApprovalType*
가 flag .

0	
1	

19. *dualAuthTimeout*
1 2 .

20. *numDualAuthApprovalGroups*
가 .

21. *reserved2*
.

22. *dualAuthApprovalGroupID*
가 16 .

23. *apbZone*
가 . [Zone Control API](#) .

From:
<https://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:
https://kb.supremainc.com/bs2sdk/doku.php?id=ko:door_control_api&rev=1470635677

Last update: **2016/08/08 14:54**