

# Table of Contents

<b>BS2_CheckGlobalAPBViolationByDoorOpen</b> .....	1
Declaration .....	1
Parameter .....	1
Return Value .....	1
See Also .....	1

 **This page is not fully translated, yet. Please help completing the translation.**  
(remove this paragraph once the translation is finished)

[Zone Control API](#) > [BS2\\_CheckGlobalAPBViolationByDoorOpen](#)

---

## BS2\_CheckGlobalAPBViolationByDoorOpen

[+ 2.7.0] Transfers Global APB by door open results to the device.

### Declaration

```
#include "BS_API.h"

int BS2_CheckGlobalAPBViolationByDoorOpen(void* context, uint32_t deviceId,
uint16_t seq, int handleResult, uint32_t zoneID);
```

### Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *seq* : Packet sequence
- [In] *handleResult* : Global Anti Passback determination result(BS\_SDK\_SUCCESS or BS\_SDK\_ERROR\_XXX)
- [In] *zoneID* : Global Anti Passback zone Id

#### NOTE

Packet sequence must be the same with the value from OnCheckGlobalAPBViolationByDoorOpen

### Return Value

If successfully done, BS\_SDK\_SUCCESS will be returned.

If there is an error, the corresponding error code will be returned.

### See Also

[BS2\\_SetGlobalAPBViolationByDoorOpenHandler](#)

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

[https://kb.supremainc.com/kbtest/doku.php?id=en:bs2\\_checkglobalapbviolationbydooropen&rev=1595988466](https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_checkglobalapbviolationbydooropen&rev=1595988466)

Last update: **2020/07/29 11:07**