

# Table of Contents

<b>BS2_GetBarcodeConfig</b> .....	1
함수 .....	1
파라미터 .....	1
반환값 .....	1

[Configuration API](#) > [BS2\\_GetBarcodeConfig](#)

---

## BS2\_GetBarcodeConfig

[+ 2.8] Retrieves configuration of Barcode of X-Station 2.

### 함수

```
#include "BS_API.h"

int BS2_GetBarcodeConfig(void* context, uint32_t deviceId, BS2BarcodeConfig* config);
```

[BS2BarcodeConfig 구조체 보기](#)

### 파라미터

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [Out] *config* : Barcode configurations pointer

### 반환값

성공적으로 수행될 경우 `BS_SDK_SUCCESS`를 반환하고, 에러가 발생할 경우 상응하는 에러 코드를 반환합니다.

From:  
<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:  
[https://kb.supremainc.com/kbtest/doku.php?id=en:bs2\\_getbarcodeconfig&rev=1622974565](https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_getbarcodeconfig&rev=1622974565)

Last update: **2021/06/06 19:16**