

Table of Contents

- BS2_GetOsdpStandardConfig** 1
- Declaration 1
- Parameter 1
- Return Value 1
- See Also 1
- Sample Code(C++) 1
- Sample Code (C#) 2

BS2_GetOsdpStandardConfig

[+ 2.9.1] Get the device's OSDP setting information.

This setting information is also used to update the master-OSDP-slave device topology configuration within the SDK.

Declaration

```
#include "BS_API.h"

int BS2_GetOsdpStandardConfig(void* context, uint32_t deviceId,
BS2OsdpStandardConfig* config);
```

[See BS2OsdpStandardConfig Structure](#)

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device Identifier
- [In] *config* : Pointer to store OSDP setting information

Return Value

If successfully done, `BS_SDK_SUCCESS` will be returned. If there is an error, the corresponding error code will be returned.

See Also

[BS2_SetOsdpStandardConfig](#)

Sample Code(C++)

[sample_getosdpstandardconfig.cpp](#)

```
BS2OsdpStandardConfig config = { , };
int sdkResult = BS2_GetOsdpStandardConfig(context_, id, &config);
if (BS_SDK_SUCCESS != sdkResult)
```

```
printf("BS2_GetOsdpStandardConfig call failed: %d", sdkResult);  
return sdkResult;
```

Sample Code (C#)

[sample_getosdpstandardconfig.cs](#)

```
BS2OsdpStandardConfig config;  
BS2ErrorCode result =  
(BS2ErrorCode)API.BS2_GetOsdpStandardConfig(sdkContext, deviceID, out  
config);  
if (result != BS2ErrorCode.BS_SDK_SUCCESS)  
    Console.WriteLine("Got error({0}).", result);  
else  
    Console.WriteLine("Call success.");  
return result;
```

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_getosdpstandardconfig&rev=1677563962

Last update: **2023/02/28 14:59**