

Table of Contents

BS2_GetSlaveExDevice	1
Declaration	1
Parameter	1
Return Value	1
See Also	1

[Slave Control API](#) > [BS2_GetSlaveDevice](#)

BS2_GetSlaveExDevice

In case of CoreStation, searches a slave device from the RS-485 network.

Declaration

```
#include "BS_API.h"

int BS2_GetSlaveExDevice(void* context, uint32_t deviceId, uint32_t
channelPort, BS2Rs485SlaveDeviceEX** slaveDevices, uint32_t* outchannelPort,
uint32_t* slaveDeviceCount);
```

[See BS2Rs485SlaveExDeviceEX Structure](#)

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *channelPort* : Channel port
- [Out] *slaveDevices* : Slave device list pointer
- [Out] *outchannelPort* : Channel port of slave device
- [Out] *slaveDeviceCount* : Number of slave devices

NOTE

slaveDeviceObj variable needs to return the memory to the system by the [BS2_ReleaseObject](#) function after being used.

Return Value

If successfully done, `BS_SDK_SUCCESS` will be returned. If there is an error, the corresponding error code will be returned.

See Also

[BS2_SetSlaveExDevice](#)

From:
<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:
https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_getslaveexdevice

Last update: **2017/09/04 16:18**