

# Table of Contents

<b>BS2_GetUserSmallInfosEx</b> .....	1
Declaration .....	1
Parameter .....	1
Return Value .....	1
See Also .....	1

 **Fix Me!** This page is not fully translated, yet. Please help completing the translation.  
(remove this paragraph once the translation is finished)

User Management API > [BS2\\_GetUserSmallInfosEx](#)

---

## BS2\_GetUserSmallInfosEx

[+ 2.6.3] Gets the user information of the given user ID with efficient use of memory.  
The only difference between [BS2\\_GetUserInfosEx](#) which is using structure [BS2UserBlob](#) is that the 3rd parameter `BS2UserPhoto` of [BS2UserSmallBlobEx](#) is using pointer for efficient memory use.

### Declaration

```
#include "BS_API.h"

int BS2_GetUserSmallInfosEx(void* context, uint32_t deviceId, char* uids,
uint32_t uidCount, BS2UserSmallBlobEx* userBlob);
```

[BS2UserSmallBlobEx 구조체 보기](#)

### Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *uids* : User ID list trying to get
- [In] *uidCount* : Number of user ID
- [Out] *userBlob* : Pointer to store the user information

### Return Value

If successfully done, `BS_SDK_SUCCESS` will be returned.  
If there is an error, the corresponding error code will be returned.

### See Also

[BS2\\_EnrollUserSmall](#)  
[BS2\\_EnrollUserSmallEx](#)  
[BS2\\_GetUserSmallInfos](#)  
[BS2\\_GetUserSmallInfosEx](#)

[BS2\\_GetUserSmallDatas](#)

[BS2\\_GetUserSmallDatasEx](#)

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

[https://kb.supremainc.com/kbtest/doku.php?id=en:bs2\\_getusersmallinfosex&rev=1560843112](https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_getusersmallinfosex&rev=1560843112)

Last update: **2019/06/18 16:31**