

Table of Contents

BS2_GetUserSmallInfosEx

Declaration

Parameter

Return Value

See Also

..... 1

..... 1

..... 1

..... 1

..... 1

BS2_GetUserSmallInfosEx

[+ 2.6.3] Gets the user information of the given user ID with efficient use of memory.

The only difference between [BS2_GetUserInfosEx](#) which is using structure [BS2UserBlob](#) is that the 3rd parameter `BS2UserPhoto` of [BS2UserSmallBlobEx](#) is using pointer for efficient memory use.

Declaration

```
#include "BS_API.h"

int BS2_GetUserSmallInfosEx(void* context, uint32_t deviceId, char* uids,
uint32_t uidCount, BS2UserSmallBlobEx* userBlob);
```

[BS2UserSmallBlobEx 구조체 보기](#)

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *uids* : User ID list trying to get
- [In] *uidCount* : Number of user ID
- [Out] *userBlob* : Pointer to store the user information

Return Value

If successfully done, `BS_SDK_SUCCESS` will be returned.

If there is an error, the corresponding error code will be returned.

See Also

[BS2_EnrollUserSmall](#)
[BS2_EnrollUserSmallEx](#)
[BS2_GetUserSmallInfos](#)
[BS2_GetUserSmallInfosEx](#)
[BS2_GetUserSmallDatas](#)
[BS2_GetUserSmallDatasEx](#)

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_getusersmallinfosex&rev=1560843121

Last update: **2019/06/18 16:32**