

# Table of Contents

***BS2\_GetUserSmallInfosFromDir***

Declaration

Parameter

Return Value

See Also

..... 1

..... 1

..... 1

..... 1

..... 1

[USB Exported Control API](#) > [BS2\\_GetUserSmallInfosFromDir](#)

---

## BS2\_GetUserSmallInfosFromDir

[+ 2.6.3] Gets the user information of the given user ID from USB exported data.

The only difference between [BS2\\_GetUserInfosFromDir](#) which is using structure [BS2UserBlob](#) is that the 5th parameter BS2UserPhoto of BS2UserSmallBlob is using pointer for efficient memory use.

### Declaration

```
#include "BS_API.h"

int BS2_GetUserSmallInfosFromDir(void* context, const char* szDir, char*
uids, uint32_t uidCount, BS2UserSmallBlob* userBlob);
```

[See BS2UserSmallBlob Structure](#)

### Parameter

- [In] *context* : Context
- [In] *szDir* : Storage path in device
- [In] *uids* : User ID list trying to get
- [In] *uidCount* : Number of user ID
- [Out] *userBlob* : Pointer to store the user information

### Return Value

If successfully done, BS\_SDK\_SUCCESS will be returned.

### See Also

[BS2\\_GetUserSmallInfosFromDir](#)  
[BS2\\_GetUserSmallDatsFromDir](#)  
[BS2\\_GetUserSmallInfosExFromDir](#)  
[BS2\\_GetUserSmallDatsExFromDir](#)

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

[https://kb.supremainc.com/kbtest/doku.php?id=en:bs2\\_getusersmallinfosfromdir](https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_getusersmallinfosfromdir)

Last update: **2019/06/18 16:29**