

# Table of Contents

<b>BS2_GetVoipConfigExt</b> .....	1
Declaration .....	1
Parameter .....	1
Return Value .....	1

[Configuration API](#) > [BS2\\_GetVoipConfigExt](#)

---

## BS2\_GetVoipConfigExt

[+ 2.8.3] Gets the extended VoIP settings.

[BS2VoipConfig](#) comparing Various settings have been added, such as specifying outbound proxy and setting the volume.

### Declaration

```
#include "BS_API.h"

int BS2_GetVoipConfigExt(void* context, uint32_t deviceId, BS2VoipConfigExt* config);
```

[See BS2VoipConfigExt View Structures](#)

### Parameter

- [In] *context* : Context
- [In] *deviceId* : Device Identifier
- [Out] *config* : Pointer to store VoIP settings information

### Return Value

If successfully done, `BS_SDK_SUCCESS` will be returned.

If there is an error, the corresponding error code will be returned.

From:

<https://kb.supremainc.com/kbtest/> - **BioStar 2 Device SDK**

Permanent link:

[https://kb.supremainc.com/kbtest/doku.php?id=en:bs2\\_getvoipconfigext](https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_getvoipconfigext)

Last update: **2024/10/24 14:47**