

Table of Contents

BS2_IdentifyUserSmall

Declaration

Parameter

Return Value

See Also

.....

.....

.....

.....

.....

1

1

1

1

2

BS2_IdentifyUserSmall

[+ 2.6.3] Transfers user information mapped to the fingerprint authentication results to the device. The only difference between with [BS2_IdentifyUser](#) which is using structure [BS2UserBlob](#) is that the 5th parameter BS2UserPhoto of BS2UserSmallBlob is using pointer for efficient memory use.

Declaration

```
#include "BS_API.h"

int BS2_IdentifyUserSmall(void* context, uint32_t deviceId, uint16_t seq,
int handleResult, BS2UserSmallBlob* userBlob);
```

[See BS2UserSmallBlob Structure](#)

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *seq* : Packet sequence number
- [In] *handleResult* : Value of matching result(BS_SDK_SUCCESS or BS_SDK_ERROR_XXX)
- [In] *userBlob* : Matched user information

Note

Packet sequence number must be equivalent to the value sent from the OnIdentifyUser.

If the handleResult is BS_SDK_SUCCESS, the userBlob should not be null.

Return Value

If successfully done, BS_SDK_SUCCESS will be returned.

See Also

[BS2_VerifyUserSmall](#)
[BS2_IdentifyUserSmall](#)
[BS2_VerifyUserSmallEx](#)
[BS2_IdentifyUserSmallEx](#)

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_identifyusersmall&rev=1560325001

Last update: **2019/06/12 16:36**