

Table of Contents

BS2_IdentifyUserSmallEx	1
Declaration	1
Parameter	1
Return Value	1
See Also	2

[Server API](#) > [BS2_IdentifyUserSmallEx](#)

BS2_IdentifyUserSmallEx

[+ 2.6.3] Transfers user information mapped to the fingerprint authentication results to the device. The only difference between with [BS2_IdentifyUserEx](#) which is using structure [BS2UserBlobEx](#) is that the 5th parameter `BS2UserPhoto` of `BS2UserBlobEx` is using pointer for efficient memory use.

Declaration

```
#include "BS_API.h"

int BS2_IdentifyUserSmallEx(void* context, uint32_t deviceId, uint16_t seq,
int handleResult, BS2UserSmallBlobEx* userBlob);
```

[See BS2UserSmallBlobEx Structure](#)

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *seq* : Packet sequence number
- [In] *handleResult* : Value of matching result(`BS_SDK_SUCCESS` or `BS_SDK_ERROR_XXX`)
- [In] *userBlob* : Matched user information

NOTE

Packet sequence number must be equivalent to the value sent from the `OnIdentifyUser`.

If the `handleResult` is `BS_SDK_SUCCESS`, the `userBlob` should not be null.

Return Value

If successfully done, `BS_SDK_SUCCESS` will be returned.

If there is an error, the corresponding error code will be returned.

See Also

[BS2_VerifyUserSmall](#)
[BS2_IdentifyUserSmall](#)
[BS2_VerifyUserSmallEx](#)
[BS2_IdentifyUserSmallEx](#)

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_identifyusersmallex&rev=1560326077

Last update: **2019/06/12 16:54**