

Table of Contents

BS2_RemoveAllAuthOperatorLevelEx	1
Declaration	1
Parameter	1
Return Value	1
See Also	1

[Device API](#) > [BS2_RemoveAllAuthOperatorLevelEx](#)

BS2_RemoveAllAuthOperatorLevelEx

[+ 2.6.3] Removes all device operators.

When using [BS2_SetAuthConfig](#), [BS2_GetAuthConfig](#), there is a limitation that you can set operators up to 10.

The new API below accommodates setting operators up to 1,000.

Caution

The existing [BS2AuthConfig](#) and operators are valid until you call the new API. However, if at any one time you call the newly added API below, the existing [BS2AuthConfig](#) setting will be ignored so you need to use only the new API and structure.

If you want to use the new API with the new structure, please move the operator list managed by existing [BS2AuthConfig](#) securely to the new structure [BS2AuthOperatorLevel](#) where can manage 1000 operators.

Declaration

```
#include "BS_API.h"

int BS2_RemoveAllAuthOperatorLevelEx(void* context, BS2_DEVICE_ID deviceId);
```

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID

Return Value

If successfully done, [BS_SDK_SUCCESS](#) will be returned. If there is an error, the corresponding error code will be returned.

See Also

[BS2_GetAuthOperatorLevelEx](#)
[BS2_GetAllAuthOperatorLevelEx](#)
[BS2_SetAuthOperatorLevelEx](#)
[BS2_RemoveAuthOperatorLevelEx](#)
[BS2_RemoveAllAuthOperatorLevelEx](#)

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_removeallauthoperatorlevelex&rev=1559529713

Last update: **2019/06/03 11:41**