

# Table of Contents

<b>BS2_RemoveCredentialKeyInfo</b> .....	1
Decalaration .....	1
Parameter .....	1
Return Value .....	1
See Also .....	1

[SDK API](#) > [BS2\\_RemoveCredentialKeyInfo](#)

## BS2\_RemoveCredentialKeyInfo

[+ V2.6.0] Removes the key setting of the device.

If the call to this function succeeds, the device will revert to the default key value, and all data on the device will be erased.

### Decalaration

```
#include "BS_API.h"

int BS2_RemoveCredentialKeyInfo(void* context, uint32_t deviceId);
```

### Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID

### Return Value

If successfully done, BS\_SDK\_SUCCESS will be returned.

If there is an error, the corresponding error code will be returned.

### See Also

[BS2\\_GetCredentialKeyInfo](#)

[BS2\\_SetCredentialKeyInfo](#)

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

[https://kb.supremainc.com/kbtest/doku.php?id=en:bs2\\_removecredentialkeyinfo&rev=1521525734](https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_removecredentialkeyinfo&rev=1521525734)

Last update: **2018/03/20 15:02**