

# Table of Contents

<b>BS2_SetBarcodeConfig</b> .....	1
Declatation .....	1
Parameter .....	1
Return Value .....	1

 **Fix Me!** This page is not fully translated, yet. Please help completing the translation.  
(remove this paragraph once the translation is finished)

[Configuration API](#) > [BS2\\_SetBarcodeConfig](#)

---

## BS2\_SetBarcodeConfig

[+ 2.8] Stores configuration of Barcode ofX-Station 2.

### Declatation

```
#include "BS_API.h"

int BS2_SetBarcodeConfig(void* context, uint32_t deviceId, BS2BarcodeConfig* config);
```

[See BS2BarcodeConfig](#)

### Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *config* : Barcode configurations pointer

### Return Value

If successfully done, BS\_SDK\_SUCCESS will be returned. If there is an error, the corresponding error code will be returned.

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

[https://kb.supremainc.com/kbtest/doku.php?id=en:bs2\\_setbarcodeconfig&rev=1622974824](https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_setbarcodeconfig&rev=1622974824)

Last update: **2021/06/06 19:20**