

# Table of Contents

<b>BS2_SetCard1xConfig</b> .....	1
Declaration .....	1
Parameter .....	1
Return Value .....	1

[Configuration API](#) > [BS2\\_SetCard1xConfig](#)

---

## BS2\_SetCard1xConfig

Stores v1 Template on Card settings on the device. This feature is implemented to read Template on Cards already issued from a v1 device. It does not allow a v2 device to issue a template on card in a v1 layout.

### Declaration

```
#include "BS_API.h"

int BS2_SetCard1xConfig(void* context, uint32_t deviceId, BS1CardConfig* config);
```

[See BS1CardConfig Structure](#)

### Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *config* : v1 template on card settings pointer

### Return Value

If successfully done, BS\_SDK\_SUCCESS will be returned.  
If there is an error, the corresponding error code will be returned.

From:  
<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:  
[https://kb.supremainc.com/kbtest/doku.php?id=en:bs2\\_setcard1xconfig](https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_setcard1xconfig)

Last update: **2017/06/28 11:04**