

# Table of Contents

<b>BS2_SetCredentialKeyInfo</b> .....	1
Declaration .....	1
Parameter .....	1
Return Value .....	1
See Also .....	1

[SDK API](#) > [BS2\\_SetCredentialKeyInfo](#)

## BS2\_SetCredentialKeyInfo

[+ V2.6.0] Sets encryption key information of the device.

If the device's key is the same as the one you are currently setting, the key setting will be ignored. Also, if the key of the device is different from the one you want to set, the key will be set and the device's data will be erased.

### Declaration

```
#include "BS_API.h"

int BS2_SetCredentialKeyInfo(void* context, uint32_t deviceId, const
BS2CredentialKeyInfo* keyInfo);
```

[See BS2CredentialKeyInfo Structure](#)

### Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *keyInfo* : The address of the key information structure to set.

### Return Value

If successfully done, BS\_SDK\_SUCCESS will be returned.

If there is an error, the corresponding error code will be returned.

### See Also

[BS2\\_GetCredentialKeyInfo](#)

[BS2\\_RemoveCredentialKeyInfo](#)

From:  
<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:  
[https://kb.supremainc.com/kbtest/doku.php?id=en:bs2\\_setcredentialkeyinfo&rev=1521525636](https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_setcredentialkeyinfo&rev=1521525636)

Last update: **2018/03/20 15:00**