

# Table of Contents

|                                                   |   |
|---------------------------------------------------|---|
| <b><i>BS2_SetDefaultResponseTimeout</i></b> ..... | 1 |
| Declaration .....                                 | 1 |
| Parameter .....                                   | 1 |
| Return Value .....                                | 1 |
| See Also .....                                    | 1 |

[Communication API](#) > [BS2\\_SetDefaultResponseTimeout](#)

---

## BS2\_SetDefaultResponseTimeout

[+ 2.6.3] Sets default response timeout between device and server. It defines timeout of every API except connection(hardcoded 3s) and BS2\_GetFilteredLog(300s).

### Declaration

```
#include "BS_API.h"

int BS2_SetDefaultResponseTimeout(void* context, long ms);
```

### Parameter

- [In] *context* : Context
- [In] *ms* : Respond waiting time (milli seconds)

### Return Value

If successfully done, BS\_SDK\_SUCCESS will be returned.  
If there is an error, the corresponding error code will be returned.

### See Also

[BS2\\_GetDefaultResponseTimeout](#)

From:  
<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:  
[https://kb.supremainc.com/kbtest/doku.php?id=en:bs2\\_setdefaultresponsetimeout&rev=1562648707](https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_setdefaultresponsetimeout&rev=1562648707)

Last update: **2019/07/09 14:05**