

# Table of Contents

<b>BS2_SetInputConfigEx</b> .....	1
API .....	1
Parameters .....	1
Return Values .....	1

 **This page is not fully translated, yet. Please help completing the translation.**  
(remove this paragraph once the translation is finished)

[Configuration API](#) > [BS2\\_SetInputConfigEx](#)

---

## BS2\_SetInputConfigEx

[+ 2.8.1] IM- 120 Saves Input Expandable Settings.

### API

```
#include "BS_API.h"

int BS2_SetInputConfigEx(void* context, uint32_t deviceId, const
BS2InputConfigEx* config);
```

[BS2InputConfigEx Structure](#)

### Parameters

- [In] *context* : Context
- [In] *deviceId* : Device Identifier
- [In] *config* : Input Expanded Setting Information Pointer

### Return Values

Return BS\_SDK\_SUCCESS when successful, and return an appropriate error code when an error occurs.

From:  
<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:  
[https://kb.supremainc.com/kbtest/doku.php?id=en:bs2\\_setinputconfigex&rev=1628205242](https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_setinputconfigex&rev=1628205242)

Last update: **2021/08/06 08:14**