

Table of Contents

BS2_SetIPConfigViaUDPEx	1
Declaration	1
Parameter	1
Return Value	1

 **Fix Me!** This page is not fully translated, yet. Please help completing the translation.
(remove this paragraph once the translation is finished)

[Configuration API](#) > [BS2_SetIPConfigViaUDPEX](#)

BS2_SetIPConfigViaUDPEX

[+ 2.6.3] Stores IP configuration through UDP broadcast with host IP.
It is useful on systems with multiple Ethernet cards installed.

Declaration

```
#include "BS_API.h"

int BS2_SetIPConfigViaUDPEX(void* context, uint32_t deviceId, const
BS2IpConfig* config, const char* hostipAddr);
```

[See BS2IpConfig Structure](#)

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *config* : IP configuration pointer
- [In] *hostipAddr* : Host IP address

Return Value

If successfully done, BS_SDK_SUCCESS will be returned.

From:
<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:
https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_setipconfigviaudpex&rev=1560820875

Last update: **2019/06/18 10:21**