

# Table of Contents

<b>BS2_VerifyUserFaceEx</b> .....	1
Declaration .....	1
Parameter .....	1
Return Value .....	1

[Server API](#) > [BS2\\_VerifyUserFaceEx](#)

---

## BS2\_VerifyUserFaceEx

[+ 2.7.2] Transfers user information mapped to the card or user ID authentication results to the device.

This API includes FaceStation F2 support.

### Declaration

```
#include "BS_API.h"

int BS2_VerifyUserFaceEx(void* context, uint32_t deviceId, uint16_t seq, int
handleResult, BS2UserFaceExBlob* userBlob);
```

[See BS2UserFaceExBlob Structure](#)

### Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *seq* : Packet sequence number
- [In] *handleResult* : Value of matching result(BS\_SDK\_SUCCESS or BS\_SDK\_ERROR\_XXX)
- [In] *userBlob* : Matched user information

#### NOTE

Packet sequence number must be equivalent to the value sent from the OnVerifyUser.

If the handleResult is BS\_SDK\_SUCCESS, the userBlob should not be null.

### Return Value

If successfully done, BS\_SDK\_SUCCESS will be returned.

If there is an error, the corresponding error code will be returned.

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

[https://kb.supremainc.com/kbtest/doku.php?id=en:bs2\\_verifyuserfaceex](https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_verifyuserfaceex)

Last update: **2020/12/15 13:17**