

Table of Contents

BS2_VerifyUserSmallEx

Declaration

Parameter

Return Value

See Also

.....

.....

.....

.....

.....

1

1

1

1

2

BS2_VerifyUserSmallEx

[+ 2.6.3] Transfers user information mapped to the card or user ID authentication results to the device.

The only difference between with [BS2_VerifyUserEx](#) which is using structure [BS2UserBlobEx](#) is that the 5th parameter BS2UserPhoto of BS2UserSmallBlob is using pointer for efficient memory use.

Declaration

```
#include "BS_API.h"

int BS2_VerifyUserSmallEx(void* context, uint32_t deviceId, uint16_t seq,
int handleResult, BS2UserSmallBlobEx* userBlob);
```

[BS2UserSmallBlobEx 구조체 보기](#)

Parameter

- [In] *context* : Context
- [In] *deviceId* : Device ID
- [In] *seq* : Packet sequence number
- [In] *handleResult* : Value of matching result(BS_SDK_SUCCESS or BS_SDK_ERROR_XXX)
- [In] *userBlob* : Matched user information

NOTE

Packet sequence number must be equivalent to the value sent from the OnVerifyUser.
If the handleResult is BS_SDK_SUCCESS, the userBlob should not be null.

Return Value

If successfully done, BS_SDK_SUCCESS will be returned.

If there is an error, the corresponding error code will be returned.

See Also

[BS2_VerifyUserSmall](#)
[BS2_IdentifyUserSmall](#)
[BS2_VerifyUserSmallEx](#)
[BS2_IdentifyUserSmallEx](#)

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

https://kb.supremainc.com/kbtest/doku.php?id=en:bs2_verifyusersmallex&rev=1560325158

Last update: **2019/06/12 16:39**