

Table of Contents

Fingerprint API	1
Structure	1
BS2Fingerprint	1

Fingerprint API

API that provides functions to scan, extract, and compare fingerprint template data.

- [BS2_ScanFingerprint](#): Scans a fingerprint from a device and extracts template data.
- [BS2_ScanFingerprintEx](#): Scans a fingerprint from a device and extracts template data and scores.
- [BS2_VerifyFingerprint](#): Compares the template data to check if it is the same finger.
- [BS2_GetLastFingerprintImage](#): Extracts the image of the last scanned fingerprint using the [BS2_ScanFingerprint](#) API.

Structure

BS2Fingerprint

```
typedef struct {  
    uint8_t index;  
    uint8_t flag;  
    uint8_t reserved[2];  
    uint8_t data[BS2_TEMPLATE_PER_FINGER][BS2_FINGER_TEMPLATE_SIZE];  
} BS2Fingerprint;
```

1. *index*

The index of finger.

2. *flag*

Flag that indicates the purpose of the fingerprint.

Value	Description
0	Normal fingerprint
1	Duress fingerprint

3. *reserved*

Reserved space.

4. *data*

The data of fingerprint template.

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

https://kb.supremainc.com/kbtest/doku.php?id=en:fingerprint_api&rev=1521095677

Last update: **2018/03/15 15:34**