

BS2_ClearAllDeviceZoneAccessRecord 1
..... 1
..... 1
..... 1
..... 1
..... 1

[Zone Control API](#) > [BS2_ClearAllDeviceZoneAccessRecord](#)

BS2_ClearAllDeviceZoneAccessRecord

Ethernet

BioStation 2 (1.5.0 only)
BioStation A2 (1.4.0 only)
BioEntry P2 (1.0.0 only)

```
#include "BS_API.h"

int BS2_ClearAllDeviceZoneAccessRecord(void* context, uint32_t deviceId,
uint32_t zoneID);
```

- [In] *context* : Context
- [In] *deviceId* :
- [In] *zoneID* :

BS_SDK_SUCCESS , 가

[BS2_GetDeviceZone](#)
[BS2_GetAllDeviceZone](#)
[BS2_SetDeviceZone](#)
[BS2_RemoveDeviceZone](#)
[BS2_SetAntiPassbackZone](#)
[BS2_RemoveAllDeviceZone](#)
[BS2_SetDeviceZoneAlarm](#)
[BS2_ClearDeviceZoneAccessRecord](#)

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

https://kb.supremainc.com/kbtest/doku.php?id=ko:bs2_clearalldevicezoneaccessrecord

Last update: **2018/03/22 10:53**