

BS2_GetAuthOperatorLevelEx

.....

1

.....

1

.....

1

.....

2

.....

2

BS2_GetAuthOperatorLevelEx

```
[+ 2.6.3]      userIDs      가      .
BS2_SetAuthConfig, BS2_GetAuthConfig      10      가
,
1000      가      .
```

BS2AuthConfig 1000 가

```
#include "BS_API.h"
```

```
int BS2_GetAuthOperatorLevelEx(void* context, BS2_DEVICE_ID deviceId,
BS2_USER_ID* userIDs, uint32_t userIDCount, BS2AuthOperatorLevel**
operatorlevelObj, uint32_t* numOperatorlevel);
```

BS2AuthOperatorLevel

- [In] *context* : Context
- [In] *deviceId* :
- [In] *userIDs* : 가
- [In] *userIDCount* :
- [Out] *operatorlevelObj* :
- [Out] *numOperatorlevel* :

operatorlevelObj

BS2_ReleaseObject



BS_SDK_SUCCESS , 가

[BS2_GetAuthOperatorLevelEx](#)
[BS2_GetAllAuthOperatorLevelEx](#)
[BS2_SetAuthOperatorLevelEx](#)
[BS2_RemoveAuthOperatorLevelEx](#)
[BS2_RemoveAllAuthOperatorLevelEx](#)

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

https://kb.supremainc.com/kbtest/doku.php?id=ko:bs2_getauthoperatorlevelex&rev=1557916824

Last update: **2019/05/15 19:40**