

BS2_GetLogFromDirWithKey 1
..... 1
..... 1
..... 1
..... 1

BS2_GetLogFromDirWithKey

[+2.8.2] USB Data ID amount 가 .

```
#include "BS_API.h"

int BS2_GetLogFromDirWithKey(void* context, const char* szDir, BS2_EVENT_ID
eventId, uint32_t amount, BS2Event** logsObj, uint32_t* numLog, const
BS2EncryptKey* key);
```

BS2Event

- [In] *context* : Context
- [In] *szDir* : Data
- [In] *eventId* : ID , 0 가 .
- [In] *amount* : , 0 eventId 가 .
- [Out] *logsObj* :
- [Out] *numLog* :
- [In] *key* : [BS2_SetDataEncryptKey](#) .

logsObj [BS2_ReleaseObject](#)

.

BS_SDK_SUCCESS , 가

[BS2_GetUserListFromDirWithKey](#)
[BS2_GetUserInfosFromDirWithKey](#)
[BS2_GetUserDatasFromDirWithKey](#)
[BS2_GetUserInfosExFromDirWithKey](#)
[BS2_GetUserDatasExFromDirWithKey](#)
[BS2_GetLogBlobFromDirWithKey](#)
[BS2_GetFilteredLogFromDirWithKey](#)

From:

<http://kb.supremainc.com/bs2sdk/> - **BioStar 2 Device SDK**

Permanent link:

http://kb.supremainc.com/bs2sdk/doku.php?id=ko:bs2_getlogfromdirwithkey

Last update: **2022/04/12 15:30**