

**BS2\_SetAuthOperatorLevelEx** ..... 1

..... 1

..... 1

..... 2

..... 2

# BS2\_SetAuthOperatorLevelEx

[+ 2.6.3]                   가 .  
 BS2\_SetAuthConfig, BS2\_GetAuthConfig                   10                   가  
 ,                   1000                   가 .

BS2AuthConfig                   ,                   1000                   가  
 ,  
 BS2AuthConfig .  
 .  
 BS2AuthConfig .  
 FW .  
 BS2 1.8.0, A2 1.7.0, L2 1.5.0, N2 1.2.0, FS 1.3.0, FaceLite 1.0.1, CS40 1.3.0, P2 1.3.0, W2 1.4.0,  
 Xpass 2 1.0.0 + 3Q 2019                   2

```
#include "BS_API.h"

int BS2_SetAuthOperatorLevelEx(void* context, BS2_DEVICE_ID deviceId,
BS2AuthOperatorLevel* operatorlevels, uint32_t operatorlevelCount);
```

BS2AuthOperatorLevel

- [In] *context* : Context
- [In] *deviceId* :
- [In] *operatorlevels* :                   가
- [In] *operatorlevelCount* :                   가

BS\_SDK\_SUCCESS , 가

[BS2\\_GetAuthOperatorLevelEx](#)  
[BS2\\_GetAllAuthOperatorLevelEx](#)  
[BS2\\_SetAuthOperatorLevelEx](#)  
[BS2\\_RemoveAuthOperatorLevelEx](#)  
[BS2\\_RemoveAllAuthOperatorLevelEx](#)

From:  
<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:  
[https://kb.supremainc.com/kbtest/doku.php?id=ko:bs2\\_setauthoperatorlevelex&rev=1610432725](https://kb.supremainc.com/kbtest/doku.php?id=ko:bs2_setauthoperatorlevelex&rev=1610432725)

Last update: **2021/01/12 15:25**