

**Communication API** ..... 1  
..... 1

# Communication API

API

LAN, USB, RS485

## BS2\_SetDeviceEventListener

- [BS2\\_SetDeviceEventListener](#): Event listener
- [BS2\\_SearchDevices](#): Subnet
- [BS2\\_SearchDevicesEx](#): IP
- [BS2\\_GetDevices](#): 가
- [BS2\\_ConnectDevice](#):
- [BS2\\_ConnectDeviceViaIP](#): IP Port
- [BS2\\_DisconnectDevice](#):
- [BS2\\_SetKeepAliveTimeout](#): Keep-alive timeout
- [BS2\\_SetNotificationListener](#): Notification listener
- [BS2\\_SetServerPort](#): Server Port
- [BS2\\_SetSSLServerPort](#): Server SSL Port
- [BS2\\_IsAutoConnection](#):
- [BS2\\_SetAutoConnection](#):

```
typedef void (*OnDeviceFound)(uint32_t deviceId);
typedef void (*OnDeviceAccepted)(BS2_DEVICE_ID deviceId);
typedef void (*OnDeviceConnected)(uint32_t deviceId);
typedef void (*OnDeviceDisconnected)(uint32_t deviceId);
typedef void (*OnAlarmFired)(BS2_DEVICE_ID deviceId, const BS2Event* event);
typedef void (*OnInputDetected)(BS2_DEVICE_ID deviceId, const BS2Event* event);
typedef void (*OnConfigChanged)(BS2_DEVICE_ID deviceId, uint32_t configMask);
```

### 1. OnDeviceFound

Subnet BioStar

### 2. OnDeviceAccepted

BioStar 가 BioStar

### 3. OnDeviceConnected

BioStar

### 4. OnDeviceDisconnected

BioStar

### 5. OnAlarmFired

Zone

### 6. OnInputDetected

가

## 7. OnConfigChanged

### Configuration

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

[https://kb.supremainc.com/kbtest/doku.php?id=ko:communication\\_api&rev=1540888150](https://kb.supremainc.com/kbtest/doku.php?id=ko:communication_api&rev=1540888150)

Last update: **2018/10/30 17:29**