

Door Control API 1

..... 1

BS2DoorRelay 1

BS2DoorSensor 1

BS2ExitButton 2

BS2DoorStatus 3

BS2Door 4

Door Control API

가 , 가 ,

- [BS2_GetDoor](#): 가 .
- [BS2_GetAllDoor](#): 가 .
- [BS2_GetDoorStatus](#): 가 .
- [BS2_GetAllDoorStatus](#): 가 .
- [BS2_SetDoor](#): .
- [BS2_SetDoorAlarm](#): .
- [BS2_RemoveDoor](#): .
- [BS2_RemoveAllDoor](#): .
- [BS2_ReleaseDoor](#): .
- [BS2_LockDoor](#): ,
- [BS2_UnlockDoor](#): ,
- [BS2_TimedLockDoor](#): [+ 2.9.12] .
- [BS2_TimedUnlockDoor](#): [+ 2.9.12] .

BS2DoorRelay

```
typedef struct {
    uint32_t deviceID;
    uint8_t port;
    uint8_t reserved[3];
} BS2DoorRelay;
```

1. *deviceID*

2. *port*

port number

3. *reserved*

BS2DoorSensor

```
typedef struct {
    uint32_t deviceID;
    uint8_t port;
    uint8_t switchType;
    uint8_t apbUseDoorSensor;
```

```

uint8_t reserved[1];
} BS2DoorSensor;

```

1. *deviceID*

2. *port*

port number

3. *switchType*

0	
1	

4. *apbUseDoorSensor*

APB door sensor

5. *reserved*

BS2ExitButton

```

typedef struct {
    uint32_t deviceID;
    uint8_t port;
    uint8_t switchType;
    uint8_t reserved[2];
} BS2ExitButton ;

```

1. *deviceID*

2. *port*

port number

3. *switchType*

0	
1	

4. *reserved*

BS2DoorStatus

```

typedef struct {
    uint32_t id;
    uint8_t opened;
    uint8_t unlocked;
    uint8_t heldOpened;
    uint8_t unlockFlags;
    uint8_t lockFlags;
    uint8_t alarmFlags;
    uint8_t reserved[2];
    uint32_t lastOpenTime;
} BS2DoorStatus;

```

1. *id*

2. *opened*

flag .

3. *unlocked*

flag .

4. *heldOpened*

flag .

5. *unlockFlags*

(OPERATOR),
 unlockFlags lockFlags (NONE) 가

0		
1		
4		
2		

6. *lockFlags*

0		
1		
4		
2		

7. *alarmFlags*

0	
1	
4	
2	APB

8. reserved

9. lastOpenTime

BS2Door

```
typedef struct {
    uint32_t doorID;
    char name[BS2_MAX_DOOR_NAME_LEN];
    uint32_t entryDeviceID;
    uint32_t exitDeviceID;
    BS2DoorRelay relay;
    BS2DoorSensor sensor;
    BS2ExitButton button;
    uint32_t autoLockTimeout;
    uint32_t heldOpenTimeout;
    uint8_t instantLock;
    uint8_t unlockFlags;
    uint8_t lockFlags;
    uint8_t unconditionalLock;
    BS2Action forcedOpenAlarm[BS2_MAX_FORCED_OPEN_ALARM_ACTION];
    BS2Action heldOpenAlarm[BS2_MAX_HELD_OPEN_ALARM_ACTION];
    uint32_t dualAuthScheduleID;
    uint8_t dualAuthDevice;
    uint8_t dualAuthApprovalType;
    uint16_t extendedAutoLockTimeout;
    uint32_t dualAuthTimeout;
    uint8_t numDualAuthApprovalGroups;
    uint8_t unused[2];
    uint8_t reserved2[1];
    uint32_t dualAuthApprovalGroupID[BS2_MAX_DUAL_AUTH_APPROVAL_GROUP];
    BS2AntiPassbackZone apbZone;
} BS2Door;
```

1. doorID

. 1 65535

2. name

BioStar . 1 가

3. entryDeviceID

4. *exitDeviceID*

5. *relay*

6. *sensor*

7. *button*

Exit

8. *autoLockTimeout*

9. *heldOpenTimeout*

10. *instantLock*

가

flag

11. *unlockFlags*

(OPERATOR),

unlockFlags

lockFlags

(NONE)

가

0		
1		
4		
2		

12. *lockFlags*

0		
1		
4		
2		

13. *unconditionalLock*

autoLock timeout

door lock

flag

0	autoLock timeout door close door lock . (door open door가 close)

1	autoLock timeout door lock door open/close

14. forcedOpenAlarm

5

15. heldOpenAlarm

5

16. dualAuthScheduleID

0

1

17. dualAuthDevice

가

flag

0	
1	
2	
3	

18. dualAuthApprovalType

가

flag

0	
1	

19. extendedAutoLockTimeout

[+ 2.9.12]

10

20. dualAuthTimeout

(:)

21. numDualAuthApprovalGroups

가

22. unused

23. reserved2

24. dualAuthApprovalGroupID

가

16

25. apbZone

가

Zone Control API

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

https://kb.supremainc.com/kbtest/doku.php?id=ko:door_control_api

Last update: **2026/01/28 16:55**