

2.4.0 1

2.4.0

2017-3-24

BioStar 2 Device SDK v2.4 가 2.4 .

v2.4

- [BS2_EnrolUserEx](#) 가 가 .
- [BS2_GetUserInfosEx](#) 가 가 .
- [BS2UserBlobEx](#) 가 가 .
- [SSL API](#)가 가 .

v2.4

BioStation 2	1.4.0
BioStation A2	1.3.0
BioStation L2	1.2.0
BioEntry W2	1.1.0

1. OM-120 SDK
API 가 가 .

- [Lift Control API](#) 가 가 .

OM-120 Lift 12 Relay door
Access group floor level floor level Access level

2. FaceStation 2 2017 2 . v2.4 FaceStation 2
7 .

- Face API 가 가

FaceStation 2 1:N Matching 5,000

3. v1 Template . v1 v2 가
 , v1 ./

- BS1CardConfig 가 가

v1 ToC(Template on Card)가 v2 . v2
 block index가 v1 CIS index block . v1 ToC v2
 Access on Card/Secure Credential Card , block index CIS index
 block

4. T&A SW Job Code가 가 . Job Code
 Job Code v2.4 FW

- BS2UserBlobEx 가 가

BS2UserBlob
 . BS2UserBlobEx Job Code v2.4 FW
 Job Code

5. 가

- API BS2_GetLogBlob 가 가
- BS2EventBlob 가 가

API BS2_GetLog Job Code 가 blob 가
 API가 blob
 가

6. FW

- BS2UserBlobEx 가 가

FaceStation 2

BS2UserBlobEx
 . BS2UserBlobEx v2.4 FW

7. SSL 가 . SSL , 가 가

- SSL API 가 가

1. **outQuality** 가 [BS2_ScanFingerprint API](#) 가 . 가 가 .
[BS2_ScanFingerprint API](#) 가 가 .
 가

BEFORE

```
#include "BS_API.h"

int BS2_ScanFingerprint(void* context, uint32_t deviceId, BS2Fingerprint*
finger, uint32_t templateIndex, uint32_t quality, uint8_t templateFormat,
OnReadyToScan ptrReadyToScan);
```

AFTER

```
#include "BS_API.h"

int BS2_ScanFingerprint(void* context, uint32_t deviceId, BS2Fingerprint*
finger, uint32_t templateIndex, uint32_t quality, uint8_t templateFormat,
uint32_t* outQuality, OnReadyToScan ptrReadyToScan);
```

2. **useJobCode, useAlphanumericID, cameraFrequency** 가 [BS2SystemConfig](#)
 가

useJobCode	Job Code	Enable/Disable	가	.
ID	BioStation 2, BioStation A2, BioStation L2	BioEntry W2	가	
		ID + Credential	가	
. v2.4 FW		useAlphanumericID </ text>		
가	ID			
A2	<text type = "success">	cameraFrequency </ text>		BioStation

<text size="x-large">3. **rs485mode, sslSupported, rootCertExist, dualIDSupported, useAlphanumericID, connectedIP, phraseCodeSupported, card1xSupported, systemExtSupported, voipSupported** 가 [BS2SimpleDeviceInfo](#) 가 .
[BS2SimpleDeviceInfo](#) 가 가 .

rs485mode	RS-485	
sslSupported	가 SSL	
rootCertExist		가
dualIDSupported	가 Dual ID	
useAlphanumericID	가 ID	
connectedIP	가	IP
phraseCodeSupported	가	

