

2.4.0 1

2.4.0

2017-3-24

BioStar 2 Device SDK v2.4

가

2.4

v2.4

- [BS2_EnrolUserEx](#) 가 가 .
- [BS2_GetUserInfosEx](#) 가 가 .
- [BS2UserBlobEx](#) 가 가 .
- [SSL API](#)가 가 .

v2.4

BioStation 2	1.4.0
BioStation A2	1.3.0
BioStation L2	1.2.0
BioEntry W2	1.1.0

1. OM-120 SDK
API 가 가 .

- [Lift Control API](#) 가 가 .

OM-120 Lift 12 Relay door
Access group floor level floor level Access level

2. FaceStation 2 2017 2 . v2.4 FaceStation 2

- [Face API](#) 가 가

FaceStation 2 1:N Matching 5,000

3. v1 Template . v1 v2 가
 , v1

- [BS1CardConfig](#) 가 가

v1 ToC(Template on Card)가 v2 . v2
 block index가 v1 CIS index block . v1 ToC v2
 Access on Card/Secure Credential Card , block index CIS index
 block

4. T&A SW Job Code가 가 . Job Code
 Job Code v2.4 FW

- [BS2UserBlobEx](#) 가 가

[BS2UserBlob](#)
[BS2UserBlobEx](#) Job Code v2.4 FW
 Job Code

5. 가

- API [BS2_GetLogBlob](#) 가 가
- [BS2EventBlob](#) 가 가

API [BS2_GetLog](#) Job Code 가 . blob 가
 API가 blob
 가

6. FW

- [BS2UserBlobEx](#) 가 가

FaceStation 2

[BS2UserBlobEx](#)
[BS2UserBlobEx](#) v2.4 FW

7. SSL 가 . SSL , 가 가

- [SSL API](#) 가 가

1. **outQuality** 가 [BS2_ScanFingerprint API](#) 가 . 가 가 .
[BS2_ScanFingerprint API](#) 가 가 .
 가

```
#include "BS_API.h"

int BS2_ScanFingerprint(void* context, uint32_t deviceId, BS2Fingerprint*
finger, uint32_t templateIndex, uint32_t quality, uint8_t templateFormat,
OnReadyToScan ptrReadyToScan);
```

```
#include "BS_API.h"

int BS2_ScanFingerprint(void* context, uint32_t deviceId, BS2Fingerprint*
finger, uint32_t templateIndex, uint32_t quality, uint8_t templateFormat,
uint32_t* outQuality, OnReadyToScan ptrReadyToScan);
```

2. **useJobCode, useAlphanumericID, cameraFrequency** 가 [BS2SystemConfig](#)

가 .
useJobCode Job Code Enable/Disable 가 .
 ID BioStation 2, BioStation A2, BioStation L2 BioEntry W2 가
 ID + Credential 가
 . v2.4 FW **useAlphanumericID**
 가 ID
cameraFrequency BioStation A2 .

3. **rs485mode, sslSupported, rootCertExist, dualIDSsupported,**
useAlphanumericID, connectedIP, phraseCodeSupported, card1xSupported,
systemExtSupported, voipSupported 가 [BS2SimpleDeviceInfo](#) 가 .
[BS2SimpleDeviceInfo](#) 가 가 .

rs485mode RS-485
sslSupported 가 SSL
rootCertExist 가
dualIDSsupported 가 Dual ID
useAlphanumericID 가 ID
connectedIP 가 IP
phraseCodeSupported 가
card1xSupported 가 v1 ToC

systemExtSupported 가 RS-485
voipSupported 가 VoIP

1. UDP 가 v2.4 FW . SDK

2. [BS2_GetConfig](#) 가 가 가
[BS2MultiWiegandConfig](#) 가 가
가

3. BioEntry Plus BioEntry W wiegand SDK
wiegand

From:
<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:
https://kb.supremainc.com/kbtest/doku.php?id=ko:release_note_240&rev=1677734678

Last update: **2023/03/02 14:24**