

2.4.0 1

2.4.0

2017-3-24

BioStar 2 Device SDK v2.4

가

2.4

v2.4

- BS2_EnrolUserEx 가 가
- BS2_GetUserInfosEx 가 가
- BS2UserBlobEx 가 가
- SSL API 가 가

v2.4

BioStation 2	1.4.0
BioStation A2	1.3.0
BioStation L2	1.2.0
BioEntry W2	1.1.0

1.

OM-120

SDK

API

가 가

- Lift Control API 가 가

OM-120 Lift

12 Relay

door

floor

가

OM-120

Access group floor level

floor level

Access level

2.

FaceStation 2 2017 2

v2.4 FaceStation 2

- Face API 가 가

FaceStation 2 1:N Matching 5,000

3. v1 Template . v1 v2 가
v1

- BS1CardConfig 가 가

v1 ToC(Template on Card)가 v2
block index가 v1 CIS index block
Access on Card/Secure Credential Card ,
block index CIS index
block

4. T&A SW Job Code가 가 . Job Code
Job Code v2.4 FW

- BS2UserBlobEx 가 가

BS2UserBlob
BS2UserBlobEx Job Code v2.4 FW
Job Code

5. . 가

- API BS2_GetLogBlob 가 가
- BS2EventBlob 가 가

API BS2_GetLog Job Code .
API가 blob 가
blob 가

6. FW

- BS2UserBlobEx 가 가

FaceStation 2

BS2UserBlobEx
BS2UserBlobEx v2.4 FW

7. SSL . SSL , . 가 . 가

- SSL API 가 가

1. **outQuality** 가 BS2_ScanFingerprint API 가
BS2_ScanFingerprint API 가 가
가

```
#include "BS_API.h"

int BS2_ScanFingerprint(void* context, uint32_t deviceId, BS2Fingerprint* finger, uint32_t templateIndex, uint32_t quality, uint8_t templateFormat, OnReadyToScan ptrReadyToScan);
```

```
#include "BS_API.h"

int BS2_ScanFingerprint(void* context, uint32_t deviceId, BS2Fingerprint* finger, uint32_t templateIndex, uint32_t quality, uint8_t templateFormat, uint32_t* outQuality, OnReadyToScan ptrReadyToScan);
```

2. **useJobCode, useAlphanumericID, cameraFrequency** 가 BS2SystemConfig
가
useJobCode Job Code Enable/Disable 가

ID	BioStation 2, BioStation A2, BioStation L2	BioEntry W2	가
v2.4 FW		ID + Credential	가
가	ID	useAlphanumericID	
cameraFrequency		BioStation A2	

3. **rs485mode, sslSupported, rootCertExist, dualIDSupported, useAlphanumericID, connectedIP, phraseCodeSupported, card1xSupported, systemExtSupported, voipSupported** 가 BS2SimpleDeviceInfo
가
BS2SimpleDeviceInfo 가 가

- **rs485mode** RS-485
- **sslSupported** 가 SSL
- **rootCertExist** 가
- **dualIDSupported** 가 Dual ID
- **useAlphanumericID** 가 ID
- **connectedIP** 가 IP
- **phraseCodeSupported** 가

- **card1xSupported** 가 v1 ToC
 - **systemExtSupported** 가 RS-485
 - **voipSupported** 가 VoIP

1. UDP 가 v2.4 FW . SDK

From: <https://kb.supremainc.com/kbtest/> - **BioStar 2 Device SDK**

Permanent link:
https://kb.supremainc.com/kbtest/doku.php?id=ko:release_note_240&rev=1681193046

Last update: **2023/04/11 15:04**