

2.4.0		1
-------	-------	---

2.4.0

2017-3-24

BioStar 2 Device SDK v2.4가 2.4 .

v2.4

- [BS2_EnrollUserEx](#)가 가 .
- [BS2_GetUserInfosEx](#)가 가 .
- [BS2UserBlobEx](#)가 가 .
- [SSL API](#)가 가 .

v2.4

BioStation 2	1.4.0
BioStation A2	1.3.0
BioStation L2	1.2.0
BioEntry W2	1.1.0

1. OM-120 SDK API가 가 .

- [Lift Control API](#)가 가 .

OM-120 Lift 12 Relay door
Access group floor level floor가 . 가 OM-120
Access level floor level Access level

2. FaceStation 2 2017 2 . v2.4 FaceStation 2
7 .

- [Face API](#) 가 가 .
- FaceStation 2 1:N Matching 5,000 .
3. v1 Template . v1 v2 가
 , v1 .
- [BS1CardConfig](#) 가 가 .
- v1 ToC(Template on Card)가 v2 . v2
block index가 v1 CIS index block . v1 ToC v2
Access on Card/Secure Credential Card , block index CIS index
block .
4. T&A SW Job Code가 가 . Job Code
Job Code . v2.4 FW .
- [BS2UserBlobEx](#) 가 가 .
- [BS2UserBlob](#)
 . [BS2UserBlobEx](#) Job Code v2.4 FW .
Job Code .
5. 가 .
- [BS2_GetLogBlob](#) 가 가 .
 - [BS2EventBlob](#) 가 가 .
- API [BS2_GetLog](#) Job Code 가 . blob 가
API가 . blob
가 .
6. FW .
- [BS2UserBlobEx](#) 가 가 .
- FaceStation 2 .
- [BS2UserBlobEx](#)
 . [BS2UserBlobEx](#) v2.4 FW .
7. SSL 가 . SSL , 가 가
- [SSL API](#) 가 가 .

1. **outQuality** 가 **BS2_ScanFingerprint** API 가 .
BS2_ScanFingerprint API 가 가 가 .

```
#include "BS_API.h"
```

```
int BS2_ScanFingerprint(void* context, uint32_t deviceId, BS2Fingerprint*  
finger, uint32_t templateIndex, uint32_t quality, uint8_t templateFormat,  
OnReadyToScan ptrReadyToScan);
```

```
#include "BS_API.h"
```

```
int BS2_ScanFingerprint(void* context, uint32_t deviceId, BS2Fingerprint*  
finger, uint32_t templateIndex, uint32_t quality, uint8_t templateFormat,  
uint32_t* outQuality, OnReadyToScan ptrReadyToScan);
```

2. **useJobCode**, **useAlphanumericID**, **cameraFrequency** 가 **BS2SystemConfig**
 가 .
useJobCode Job Code Enable/Disable 가 .

ID BioStation 2, BioStation A2, BioStation L2 BioEntry W2 가
 ID + Credential 가
 v2.4 FW **useAlphanumericID**
 가 ID
cameraFrequency BioStation A2 .

3. **rs485mode**, **sslSupported**, **rootCertExist**, **dualIDSupported**,
useAlphanumericID, **connectedIP**, **phraseCodeSupported**, **card1xSupported**,
systemExtSupported, **voipSupported** 가 **BS2SimpleDeviceInfo** 가 .
BS2SimpleDeviceInfo 가 가 .

- **rs485mode** RS-485 .
- **sslSupported** 가 SSL .
- **rootCertExist** 가 .
- **dualIDSupported** 가 Dual ID .
- **useAlphanumericID** 가 ID .
- **connectedIP** 가 IP .
- **phraseCodeSupported** 가 .

- **card1xSupported** 가 v1 ToC
- **systemExtSupported** 가 RS-485
- **voipSupported** 가 VoIP

1. UDP 가 v2.4 FW . SDK

2. [BS2_GetConfig](#) 가 . 가 가
[BS2MultiWiegandConfig](#) . 가 가
 가 .

3. BioEntry Plus BioEntry W wiegand SDK
 wiegand .

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

https://kb.supremainc.com/kbtest/doku.php?id=ko:release_note_240&rev=1681193389

Last update: **2023/04/11 15:09**