

2.9.6

(V2.9.6.0)

.....

.....

.....

.....

1

1

1

2

2.9.6 (V2.9.6.0)

2024-02-05

- BioEntry W3 (BEW3-DB, BEW3-APB)
- XPass 2 가 (XP2-MAPB)
-
- wiegand , 가
- 가
- /
- RS485 baudrate 가
- 가

1.

- BioEntry W3 (BEW3-DB, BEW3-APB)
- XPass 2 (XP2-MAPB)

2. 가 . 가 .

가
BioStation 3, FaceStation F2, BioEntry W3 visual face

- BS2FaceConfig
- BS2FaceEx

3. 가 wiegand ,

가 .

- BS2Trigger
- BS2DeviceCapabilities

5. 가 , 가 LED command 가 .

- BS2DisplayConfig
- BS2DeviceCapabilities

6. RS485 baudrate 가 .

- BS2 SetSlaveBaudrate 가

7. 가 가 .

- [BS2_InitializeEx](#) 가

1. CoreStation 40 face configuration 가 , BS_SDK_ERROR_NOT_SUPPORTED
가 .

* [BS2_GetFaceConfig](#) * [BS2_SetFaceConfig](#) * [BS2FaceConfig](#)

2. [BS2_GetFilteredLogSinceEventId](#)가
[BS2_GetLog](#) [BS2_StartMonitoringLog](#) .

* [BS2_GetFilteredLogSinceEventId](#) * [BS2_GetLog](#) * [BS2_StartMonitoringLog](#)
* [BS2_StopMonitoringLog](#)

3. SDK

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

https://kb.supremainc.com/kbtest/doku.php?id=ko:release_note_296&rev=1708408803

Last update: **2024/02/20 15:00**