

2.9.8 **(v2.9.8.0)** 1
 1
 1
 2

2.9.8 (v2.9.8.0)

2024-9-30

- ID,
- BioStation 3 IP SIP
- BioStation 3 IP , RTSP
- 가
- X-Station 2 PIN 가 가
- 가
- CoreStation Aux Input 가 가

1. ID 가

- [BS2DisplayConfig](#) - authMsgUserName, authMsgUserID

2. BioStation 3 IP UDP, TCP, TLS 가

- [BS2VoipConfigExt](#) - transport (: BioStation 3)

3. BioStation 3 IP RTSP 가

- [BS2VoipConfigExt](#) - resolution (: BioStation 3)
- [BS2RtspConfig](#) - resolution (: BioStation 3, BioEntry W3)

4. BioStation 3, FaceStation F2, BioEntry W3 가

- [BS2FaceConfigExt](#) - maskCheckMode
- [BS2DeviceCapabilities](#) - authDenyMaskSupported

5. X-Station 2 PIN 가

- [BS2DisplayConfig](#) - scrambleKeyboardMode
- [BS2DeviceCapabilities](#) - scrambleKeyboardModeSupported

6. CoreStation40 Aux Input 가 .

- [BS2InputConfig](#) - aux

1. C++(x64) BS2_ReleaseContext() 가 .

2. BS2_SetAutoConnection , 가

3. so Linux Library SONAME .

4. BS2_RS485Config, BS2_RS485ConfigEx mode 'Not use'가

5. C#

- ConfigControl getDeviceCapabilities()
- UserControl imagedata .
- SlaveControl wiegandDeviceID .

From: <https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link: https://kb.supremainc.com/kbtest/doku.php?id=ko:release_note_298&rev=1729581425

Last update: **2024/10/22 16:17**