

2.9.8     **(v2.9.8.0)** ..... 1  
          ..... 1  
          ..... 1  
          ..... 2

# 2.9.8 (v2.9.8.0)

2024-9-30

- ID,
- BioStation 3 IP SIP
- BioStation 3 IP , RTSP
- 가
- X-Station 2 PIN 가 가
- RS-485 가
- CoreStation Aux Input 가

## 1. ID 가

- [BS2DisplayConfig](#) - authMsgUserName, authMsgUserID

## 2. BioStation 3 IP UDP, TCP, TLS 가

- [BS2VoipConfigExt](#) - transport ( : BioStation 3)

## 3. BioStation 3 IP RTSP 가

- [BS2VoipConfigExt](#) - resolution ( : BioStation 3)
- [BS2RtspConfig](#) - resolution ( : BioStation 3, BioEntry W3)

## 4. 가

BioStation 3, FaceStation F2, BioEntry W3

- [BS2FaceConfigExt](#) - maskCheckMode
- [BS2DeviceCapabilities](#) - authDenyMaskSupported

## 5. X-Station 2 PIN 가

- [BS2DisplayConfig](#) - scrambleKeyboardMode
- [BS2DeviceCapabilities](#) - scrambleKeyboardModeSupported

6. RS-485 가 .

- BS2\_SetSlaveBaudrate 가

7. CoreStation40 Aux Input 가 .

- [BS2InputConfig](#) - aux

1. C++(x64) BS2\_ReleaseContext() 가 .

2. BS2\_SetAutoConnection , 가

3. so Linux Library SONAME .

4. BS2\_RS485Config, BS2\_RS485ConfigEx mode 'Not use'가

5. C#

- ConfigControl `getDeviceCapabilities()`
- UserControl `imagedata` .
- SlaveControl `wiegandDeviceID` .

From: <https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link: [https://kb.supremainc.com/kbtest/doku.php?id=ko:release\\_note\\_298&rev=1729664761](https://kb.supremainc.com/kbtest/doku.php?id=ko:release_note_298&rev=1729664761)

Last update: **2024/10/23 15:26**