

SDK API 1
..... 1
 BS2Handshake 1

SDK API

PIN

API

- [BS2_Version](#): SDK
- [BS2_AllocateContext](#): Context
- [BS2_ReleaseContext](#): Context
- [BS2_Initialize](#): Context
- [BS2_ReleaseObject](#):
- [BS2_MakePinCode](#): PIN
- [BS2_SetMaxThreadCount](#):
- [BS2_ComputeCRC16CCITT](#): CRC-16 CCITT
- [BS2_GetCardModel](#): 가
- [BS2_GetCredentialKey](#): 가
- [BS2_SetCredentialKey](#):
- [BS2_RemoveCredentialKey](#):

BS2Handshake

```
enum {
    BS2_HANDSHAKE_KEY_SIZE = 32,
};

/**
 * BS2Handshake
 */
typedef struct {
    uint32_t maxPacketSize;           ///< 4 bytes
    uint8_t  key[BS2_HANDSHAKE_KEY_SIZE];  ///< 32 bytes
    bool     dualIDSupported;         ///< 1 byte
    bool     useAlphanumericID;      ///< 1 byte
    bool     credentialKeySupported;  ///< 1 byte
    bool     credentialKeyRequired;  ///< 1 byte
    bool     discoverySession;       ///< 1 byte
    uint8_t  reserved[27];           ///< 27 bytes (reserved)
} BS2Handshake;
```

1. *maxPacketSize*

가 TCP

2. *key*

DB

3. *dualIDSupported*

userID (,) .

4. *useAlphanumericID*

alphanumeric userID

flag .

5. *credentialKeySupported*

6. *credentialKeyRequired*

7. *discoverySession*

8. *reserved*

From:

<https://kb.supremainc.com/kbtest/> - **BioStar Device SDK**

Permanent link:

https://kb.supremainc.com/kbtest/doku.php?id=ko:sdk_api&rev=1520926930

Last update: **2018/03/13 16:42**