

SDK API	1
	1
BS2CredentialKeyInfo	1

SDK API

PIN

API

- **BS2_Version:** SDK
- **BS2_AllocateContext:** Context
- **BS2_ReleaseContext:** Context
- **BS2_Initialize:** Context
- **BS2_ReleaseObject:**
- **BS2_MakePinCode:** PIN
- **BS2_SetMaxThreadCount:**
- **BS2_ComputeCRC16CCITT:** CRC-16 CCITT
- **BS2_GetCardModel:** 가
- **BS2_GetCredentialKey:** 가
- **BS2_SetCredentialKey:**
- **BS2_RemoveCredentialKey:**

BS2CredentialKeyInfo

```
/**  
 * BS2_CRED_KEY_REQ  
 */  
enum  
{  
    BS2_CRED_KEY_REQ_COMM = ,  
    BS2_CRED_KEY_REQ_DATA = 1,  
};  
  
enum  
{  
    BS2_CRED_KEY_SIZE = 32,  
};  
  
/**  
 * BS2CredentialKeyInfo  
 */  
typedef struct  
{  
    uint32_t maxPacketSize;           ///< 4 bytes  
    uint8_t key[BS2_CRED_KEY_SIZE];   ///< 32 bytes  
    bool dualIDSupported;          ///< 1 byte  
    bool useAlphanumericID;        ///< 1 byte  
    bool credentialKeySupported;    ///< 1 byte
```

```
BS2_CRED_KEY_REQ credentialKeyRequest; ///< 1 byte
    uint8_t reserved[28];           ///< 28 bytes (reserved)
} BS2CredentialKeyInfo;
```

1. maxPacketSize

가 TCP

2. key

credentialKeyRequest

3. dualIDSupported

userID (,)

4. useAlphanumericID

alphanumeric userID flag

5. credentialKeySupported

FW release 가 2018.03.30

가

6. credentialKeyRequest

FW release 가 2018.03.30

FW

BS2_CRED_KEY_REQ_COMM	
BS2_CRED_KEY_REQ_DATA	

7. reserved

From:

<https://kb.supremainc.com/kbtest/> - BioStar 2 Device SDK

Permanent link:

https://kb.supremainc.com/kbtest/doku.php?id=ko:sdk_api&rev=1520947386

Last update: **2018/03/13 22:23**