

# Table of Contents

SDK API

Structure

BS2EncryptKey

1

1

1

# SDK API

The followings are a set of APIs that initialize device management information and that are used for dynamic memory control and PIN code generation.

- [BS2\\_Version](#): Returns the SDK version.
- [BS2\\_AllocateContext](#): Allocates the device management Context.
- [BS2\\_ReleaseContext](#): Releases the device management Context.
- [BS2\\_Initialize](#): Initializes the device management Context.
- [BS2\\_ReleaseObject](#): Releases dynamic memory.
- [BS2\\_MakePinCode](#): Encrypts the PIN.
- [BS2\\_SetMaxThreadCount](#): Specifies the maximum thread count.
- [BS2\\_ComputeCRC16CCITT](#): Calculates the CRC-16 CCITT checksum.
- [BS2\\_GetCardModel](#): Retrieves the supported card models.
- [BS2\\_GetDataEncryptKey](#): Gets the encryption key for the device.
- [BS2\\_SetDataEncryptKey](#): Sets the encryption key for the device.
- [BS2\\_RemoveDataEncryptKey](#): Removes the encryption key for the device.
- [BS2\\_SetDeviceSearchingTimeout](#) : Specifies the device searching time.
- [BS2\\_SetDebugFileLog](#) : Retrieves debugging file log.

## Structure

### BS2EncryptKey

```
enum
{
    BS2_ENC_KEY_SIZE = 32,
};

typedef struct
{
    uint8_t key[BS2_ENC_KEY_SIZE];
    uint8_t reserved[32];
} BS2EncryptKey;
```

1. *key*

The key value used by the device.

2. *reserved*

Reserved space.

From:

<https://kb.supremainc.com/kbtest/> - **BioStar 2 Device SDK**

Permanent link:

[https://kb.supremainc.com/kbtest/doku.php?id=en:sdk\\_api&rev=1559521101](https://kb.supremainc.com/kbtest/doku.php?id=en:sdk_api&rev=1559521101)

Last update: **2019/06/03 09:18**