
.....	1
.....	1
.....	1
.....	1
.....	2
.....	2
.....	2
.....	3
.....	3
.....	3
.....	3
.....	3
.....	3
.....	3
.....	4

System Configuration



BioStar 2

BioStar 2

-
-
-

-
-
-
-
-
-
-
-
-
-

- [BioStar 2](#)
-
- [HTTP HTTPS](#)
- [BioStar 2](#)
- [16](#)
-

- BioStar 2
- (Daylight Saving Time)
- ID, ID,
- USB BioStar 2
- BioStar 1.x to BioStar 2.x Migration Tool

- CSN Wiegand
- Wiegand
- ID /
- BioStar 2

- 가
- CoreStation Wiegand CoreStation
- DM-20 LED
- Wiegand
- (TLS/SSL)
- SIP ID
- XPass D2
- One Device(Legacy) Mode
- Wiegand
- XPass D2 (XPD2-GKDB)

-
- 가

- (APB)
-
- /
-
-
-

- BioStar 2

-
-
-
-
-
-
-
-
- [가]
- 가 /
- BioStar 2
-
-
- 24

-
-
-
-
-
-
-
-

-
-

- BioStar 2 Mobile
- BioStar 2 Mobile

- [BioMini](#)
- [How to issue and use mobile smart cards](#)
- [BioStar 2 Mobile](#)
- [BioStar 2 Mobile](#)
- [Device Manager](#)

-
-
-
-
-
-
-
-
- [\(AoC\)](#)
-
- [DESFire EV1](#)

From:
<https://kb.supremainc.com/knowledge/> -

Permanent link:
https://kb.supremainc.com/knowledge/doku.php?id=ko:trn_config_main&rev=1568189529

Last update: **2019/09/11 17:12**