

---

.....	1
.....	1
.....	1
.....	1
.....	2
.....	2
.....	3
.....	3
.....	3
.....	3
.....	3
.....	3
.....	3
.....	3
.....	3
.....	4
.....	4

# System Configuration



BioStar 2

BioStar 2

- 
- 
- 

- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 

- [BioStar 2](#)
- 
- [HTTP HTTPS](#)
- [BioStar 2](#)
- [16](#)

- 
- BioStar 2
- (Daylight Saving Time)
- ID, ID,
- USB BioStar 2
- BioStar 1.x to BioStar 2.x Migration Tool

- 
- CSN Wiegand
- 
- Wiegand
- 
- ID
- /
- 
- BioStar 2

- 가
- CoreStation
- Wiegand CoreStation
- 
- DM-20
- LED
- 
- Wiegand
- 
- 
- (TLS/SSL)
- 
- SIP ID
- XPass D2
- 
- One Device(Legacy) Mode
- 
- Wiegand
- 
- XPass D2 (XPD2-GKDB)
- 
-

- 

- 
- 가

- (APB)
- 
- /
- 
- 
- 

- BioStar 2

- 
- 
- 
- 
- 
- 
- 

- [ 가 ] /

- BioStar 2

- 
- 

- 24

- 
- 가
- 
- 
- 
- 

- 
-

- BioStar 2 Mobile
- BioStar 2 Mobile
- BioMini
- How to issue and use mobile smart cards
- BioStar 2 Mobile
- BioStar 2 Mobile
- Device Manager

- 
- 
- 
- 
- 
- 
- 
- 
- (AoC)
- 
- DESFire EV1

From:  
<https://kb.supremainc.com/knowledge/> -

Permanent link:  
[https://kb.supremainc.com/knowledge/doku.php?id=ko:trn\\_config\\_main&rev=1569552078](https://kb.supremainc.com/knowledge/doku.php?id=ko:trn_config_main&rev=1569552078)

Last update: **2019/09/27 11:41**