
.....	1
.....	1
.....	1
.....	1
.....	2
.....	2
.....	3
.....	3
.....	3
.....	3
.....	3
.....	3
.....	4
.....	4
.....	4

System Configuration



BioStar 2

BioStar 2

-
-
-

-
-
-
-
-
-
-
-
-
-
-
-

- [BioStar 2](#)
-
- [HTTP HTTPS](#)
- [BioStar 2](#)
- [16](#)

-
- BioStar 2
- (Daylight Saving Time)
- ID, ID,
- USB BioStar 2
- BioStar 1.x to BioStar 2.x Migration Tool
- BioStar 2 가
- 'setting.conf'

-
- CSN Wiegand
-
- Wiegand
-
- ID
- /
-
- BioStar 2
-

- 가
- CoreStation
- Wiegand CoreStation
-
- DM-20
- LED
- Wiegand
-
-
- (TLS/SSL)
-
- SIP ID
- XPass D2
-
- One Device(Legacy) Mode
-
- Wiegand
-
- XPass D2 (XPD2-GKDB)
-
-

- [Wiegand](#)

- ()
-

-

-
- 가

- (APB)
-
- /
-
-
-

- [BioStar 2](#)

-
-
-
-
-
-
-
-

- [가] /

- [BioStar 2](#)

-
-

- 24

-
- 가
-
-
-
-

-
-

- BioStar 2 Mobile
- BioStar 2 Mobile
- BioMini
- BioStar 2 Mobile
- BioStar 2 Mobile
- Device Manager

-
-
-
-
-
-
-
-
- (AoC)
-
- DESFire EV1
- test

From:
<http://kb.supremainc.com/knowledge/> -

Permanent link:
http://kb.supremainc.com/knowledge./doku.php?id=ko:trn_config_main&rev=1610351307

Last update: **2021/01/11 16:48**